

Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

AIR HOSE WRAPPED SURFACE
400PSI

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
CAH4-005	3/16"	4.8	12	28	400	84	1200	100	330
CAH4-006	1/4"	6.4	13	28	400	84	1200	100	330
CAH4-008	5/16"	7.9	15	28	400	84	1200	100	330
CAH4-010	3/8"	9.5	17	28	400	84	1200	100	330
CAH4-012	1/2"	12.7	23	28	400	84	1200	100	330
CAH4-019	3/4"	19.1	30	28	400	84	1200	100	330
CAH4-025	1"	25.4	37	28	400	84	1200	100	330
CAH4-032	1-1/4"	31.8	46	28	400	84	1200	60	200
CAH4-038	1-1/2"	38.1	52	28	400	84	1200	60	200
CAH4-050	2"	50.8	68	28	400	84	1200	60	200

- 1.Tube and Cover: Rubber,smooth or wrapped, oil resistance
- 2.Reinforcement: 1ply or 2ply polyester thread braiding
- 3.Application: For air, oil and medium grade fuels used in construction, shipyards, mining and agriculture.
- 4.Temperature: -30°C (- 22°F) to + 80°C (+ 176°F)

Rubber Multipurpose Hose 300PSI

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
MPH-005	3/16"	4.8	12	20	300	60	900	100	330
MPH-006	1/4"	6.4	13	20	300	60	900	100	330
MPH-008	5/16"	7.9	15	20	300	60	900	100	330
MPH-010	3/8"	9.5	17	20	300	60	900	100	330
MPH-012	1/2"	12.7	21	20	300	60	900	100	330
MPH-016	5/8"	15.9	26	20	300	60	900	100	330
MPH-019	3/4"	19.1	29	20	300	60	900	100	330
MPH-025	1"	25.4	36	20	300	60	900	100	330
MPH-032	1-1/4"	31.8	44	15	225	45	675	60	200
MPH-038	1-1/2"	38.1	54	15	225	45	675	60	200
MPH-050	2"	50.8	66	15	225	45	675	60	200

- 1.Tube and Cover: Oil resistant Rubber ,smooth, oil resistance
- 2.Reinforcement: 1ply or 2ply polyester thread braiding
- 3.Application: For air, oil and medium grade fuels used in construction, shipyards, mining and agriculture.
- 4.Temperature: -30°C (- 22°F) to + 80°C (+ 176°F)

TPR(Rubber & Pvc Mixed)
Multipurpose Hose 300PSI

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
RTPR--06	1/4"	6	12	20	300	60	900	100	0.114
RTPR--08	5/16"	8	15	20	300	60	900	100	0.171
RTPR--10	3/8"	10	17	20	300	60	900	100	0.2
RTPR--13	1/2"	13	22	20	300	60	900	50	0.334
RTPR--16	5/8"	16	25	20	300	60	900	50	0.391
RTPR--19	3/4"	19	28	20	300	60	900	50	0.448
RTPR--25	1"	25	35	20	300	60	900	50	0.636

- 1.Tube and Cover: Rubber or TPR (NBR/PVC),smooth, oil resistance
- 2.Reinforcement: 1ply or 2ply polyester thread braiding
- 3.Application: For air, oil and medium grade fuels used in construction, shipyards, mining and agriculture.
- 4.Temperature: -30°C (- 22°F) to + 80°C (+ 176°F)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
JAH-019	3/4"	19.1	29	20	300	60	900	100	330
JAH-025	1"	25.4	36	20	300	60	900	100	330

- 1.Tube: NR & SBR synthetic rubber, black color.
- 2.Reinforcement:1ply or 2ply high tensile polyester thread braiding
- 3.Cover: NR & SBR synthetic rubber,smooth or wrapped surface, black,yellow,red available
- 4.Application: For jackhammer applications.
- 5.Temperature: -40°C (-104 ℉)to 70°C (+158 ℉)

JACK HAMMER AIR HOSE

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
CAH6-012	1/2"	12.7	23	42	600	126	1800	30.5	100
CAH6-019	3/4"	19.1	30	42	600	126	1800	30.5	100
CAH6-025	1"	25.4	37	42	600	126	1800	30.5	100
CAH6-032	1- 1/4"	31.8	46	42	600	126	1800	30.5	100
CAH6-038	1- 1/2"	38.1	52	42	600	126	1800	30.5	100
CAH6-050	2"	50.8	68	42	600	126	1800	30.5	100
CAH6-064	2- 1/2"	63.5	80	42	600	126	1800	30.5	100
CAH6-076	3"	76.2	92	42	600	126	1800	30.5	100
CAH6- 102	4"	101.6	123	42	600	126	1800	30.5	100
CAH6- 152	6"	152	175	42	600	126	1800	30.5	100

- 1.Tube: NR & SBR synthetic rubber, black color.
- 2.Reinforcement: High tensile steel wire braiding or spiral
- 3.Cover: NR & SBR synthetic rubber, black, yellow,gray available
- 4.Application: For heavy duty air supply where high temperature is required. For use with high-temperature compressors without an after-cooler, mining, quarries, construction, industrial air placement, sand blasting and heavy duty equipment.
- 5.Temperature: - 30°C (-22°F) to + 80°C (+176°F)

WIRE REINFORCED AIR HOSE
600 PSI

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
HABH038	1-1/2"	38	50	10	150	30	450	61	200
HABH050	2"	50.8	64	10	150	30	450	61	200
HABH064	2-1/2"	64	76	10	150	30	450	61	200
HABH076	3"	76.2	91	10	150	30	450	61	200
HABH089	3-1/2"	89	104	7	100	21	300	61	200
HABH102	4"	102	120	5	75	15	225	61	200
HABH127	5"	127	144	5	75	15	225	61	200
HABH152	6"	152	170	5	75	15	225	30.5	100

- 1.Tube: Black EPDM
- 2.Reinforcement: Multiple plies of polyester tire cord with wire helix Cover: Black heat resistant EPDM rubber
- 3.Application:Hot Air Blower flexible lightweight hose
- 4.designed for transferring hot air to tanks on dry bulk material trucks.
- 5.Temperature: -30°F (-35°C) to +300°F (+149°C) up to 325°F (+177°C) on an intermittent basis. Not for steam service

HOT AIR BLOWER HOSE

Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

WATER DISCHARGE HOSE
150 PSI



- 1.Tube:Black,smooth,NR,SBR rubber compound.
- 2.Reinforcement:Multiple high strength synthetic fibre
- 3.Cover:Black,smooth,cloth impression, SBR rubber compound
- 4.Temperature:-40℃ (-104 ℉) + 70℃ (+158 ℉)
- 5.Application:Designed for water and non-corrosive fluids used i and light duty industrial applications.

WATER DISCHARGE HOSE
300 PSI



- 1.Tube:Black,smooth,NR,SBR rubber compound.
- 2.Reinforcement:Multiple high strength synthetic fibre
- 3.Cover:Black,smooth,cloth impression, SBR rubber compound
- 4.Temperature:-40℃ (-104 ℉) + 70℃ (+158 ℉)
- 5.Application:Designed for water and non-corrosive fluids used i and light duty industrial applications.

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
WDH1-005	3/16"	4.8	12	10	150	30	450	100	330
WDH1-006	1/4"	6.4	13	10	150	30	450	100	330
WDH1-008	5/16"	7.9	15	10	150	30	450	100	330
WDH1-009	3/8"	9.5	16	10	150	30	450	100	330
WDH1-012	1/2"	12.7	22	10	150	30	450	100	330
WDH1-016	5/8"	15.9	26	10	150	30	450	100	330
WDH1-019	3/4"	19.1	29	10	150	30	450	100	330
WDH1-022	7/8"	22.2	32	10	150	30	450	100	330
WDH1-025	1"	25.4	35	10	150	30	450	100	330
WDH1-032	1-1/4"	31.8	42	10	150	30	450	60	200
WDH1-038	1-1/2"	38.1	48	10	150	30	450	60	200
WDH1-050	2"	50.8	62	10	150	30	450	60	200
WDH1-063	2-1/2"	63.5	76	10	150	30	450	60	200
WDH1-076	3"	76.2	89	10	150	30	450	60	200
WDH1-089	3-1/2"	88.9	103	10	150	30	450	60	200
WDH1-102	4"	101.6	116	10	150	30	450	60	200
WDH1-127	5"	127	142	10	150	30	450	30	100
WDH1-152	6"	152.4	167	10	150	30	450	30	100
WDH1-203	8"	203.2	219	10	150	30	450	30	100
WDH1-254	10"	254	274	10	150	30	450	12	40
WDH1-305	12"	304.8	322	10	150	30	450	12	40

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
WDH2-005	3/16"	4.8	12	20	300	60	900	100	330
WDH2-006	1/4"	6.4	13	20	300	60	900	100	330
WDH2-008	5/16"	7.9	15	20	300	60	900	100	330
WDH2-009	3/8"	9.5	16	20	300	60	900	100	330
WDH2-012	1/2"	12.7	22	20	300	60	900	100	330
WDH2-016	5/8"	15.9	26	20	300	60	900	100	330
WDH2-019	3/4"	19.1	29	20	300	60	900	100	330
WDH2-025	1"	25.4	36	20	300	60	900	100	330
WDH2-032	1- 1/4"	31.8	44	17	250	51	750	60	200
WDH2-038	1- 1/2"	38.1	51	17	250	51	750	60	200
WDH2-050	2"	50.8	65	17	250	51	750	60	200
WDH2-063	2- 1/2"	63.5	78	17	250	51	750	60	200
WDH2-076	3"	76.2	91	17	250	51	750	60	200
WDH2-089	3- 1/2"	88.9	108	17	250	51	750	60	200
WDH2- 102	4"	101.6	120	17	250	51	750	60	200
WDH2- 127	5"	127	148	17	250	51	750	30	100
WDH2- 152	6"	152.4	173	17	250	51	750	30	100
WDH2-203	8"	203.2	228	17	250	51	750	30	100
WDH2-254	10"	254	280	17	250	51	750	12	40
WDH2-304	12"	304.8	330	17	250	51	750	12	40

Item Code	I.D		O.D	W.P		B.P		vacuum	L	
	inch	mm	mm	bar	psi	bar	psi	bar	m	ft
WSDH-019	3/4"	19.1	30	10	150	30	450	0.8	60	200
WSDH-025	1"	25.4	36	10	150	30	450	0.8	60	200
WSDH-032	1- 1/4"	31.8	44	10	150	30	450	0.8	60	200
WSDH-038	1- 1/2"	38.1	51	10	150	30	450	0.8	60	200
WSDH-050	2"	50.8	64	10	150	30	450	0.8	60	200
WSDH-063	2- 1/2"	63.5	77	10	150	30	450	0.8	60	200
WSDH-076	3"	76.2	90	10	150	30	450	0.8	60	200
WSDH-089	3- 1/2"	88.9	104	10	150	30	450	0.8	60	200
WSDH- 102	4"	101.6	118	10	150	30	450	0.8	30	200
WSDH- 127	5"	127	145	10	150	30	450	0.8	30	100
WSDH- 152	6"	152.4	170	10	150	30	450	0.8	30	100
WSDH-203	8"	203.2	224	10	150	30	450	0.8	30	100
WSDH-276	10"	254	276	10	150	30	450	0.8	12	40
WSDH-326	12"	304	326	10	150	30	450	0.8	12	40
WSDH-378	14"	350	378	10	150	30	450	0.8	12	40

Item Code	I.D		O.D	W.P		B.P		vacuum	L	
	inch	mm	mm	bar	psi	bar	psi	bar	m	ft
WSH2-019	3/4"	19.1	31	20	300	60	900	0.8	60	200
WSH2-025	1"	25.4	38	20	300	60	900	0.8	60	200
WSH2-032	1- 1/4"	31.8	47	20	300	60	900	0.8	60	200
WSH2-038	1- 1/2"	38.1	53	20	300	60	900	0.8	60	200
WSH2-050	2"	50.8	67	20	300	60	900	0.8	60	200
WSH2-063	2- 1/2"	63.5	82	20	300	60	900	0.8	60	200
WSH2-076	3"	76.2	94	20	300	60	900	0.8	60	200
WSH2-089	3- 1/2"	88.9	110	20	300	60	900	0.8	60	200
WSH2- 102	4"	101.6	122	20	300	60	900	0.8	60	200
WSH2- 127	5"	127	150	20	300	60	900	0.8	30	100
WSH2- 152	6"	152.4	176	20	300	60	900	0.8	30	100
WSH2-203	8"	203.2	232	20	300	60	900	0.8	12	40
WSH2-254	10"	254	290	20	300	60	900	0.8	12	40
WSH2-304	12"	304	340	20	300	60	900	0.8	12	40

Item Code	I.D		O.D	W.P		B.P		L	Weight
	inch	mm	mm	bar	psi	bar	psi	m	kg/m
RFS-05	3/16"	5	12	20	300	60	900	100	0.15
RFS-06	1/4"	6	13	20	300	60	900	100	0.17
RFS-08	5/16"	8	15	20	300	60	900	100	0.22
RFS-10	3/8"	10	17	20	300	60	900	100	0.25
RFS-13	1/2"	13	22	20	300	60	900	100	0.46
RFS-16	5/8"	16	25	20	300	60	900	50	0.52
RFS-19	3/4"	19	29	20	300	60	900	50	0.64
RFS-25	1"	25	36	20	300	60	900	50	0.85
RFS-32	1-1/4"	32	43	10	150	30	450	50	1.2
RFS-38	1-1/2"	38	50	10	150	30	450	50	1.39
RFS-51	2"	51	65	10	150	30	450	50	1.8

WATER SUCTION HOSE 150 PSI



- 1.Tube:Black,smooth,NR,SBR rubber compound.
- 2.Reinforcement:Multiple High strength synthetic fibre and helix steel wire
- 3.Cover:Black,smooth,cloth impression, SBR rubber compound
- 4.Temperature: -30℃ (- 22°F) to + 80℃ (+ 176°F)
- 5.Application: Hard-wall hose designed for suction and discharge of water,and non-corrosive fluids used in construction sites and light duty industrial applications. Ideal high pressure water discharge hose for rugged, tough operating conditions

WATER SUCTION HOSE 300 PSI



- 1.Tube:Black,smooth,NR,SBR rubber compound.
- 2.Reinforcement:Multiples High strength synthetic fibre and helix steel wire
- 3.Cover:Black,smooth,cloth impression, SBR rubber compound
- 4.Temperature: -30℃ (- 22°F) to + 80℃ (+ 176°F)
- 5.Application: Hard-wall hose designed for suction and discharge of water,and non-corrosive fluids used in construction, mines,and light duty industrial

NITRILE FUEL OIL HOSE
300 PSI



- 1.Tube: Black,smooth,NBR rubber.
- 2.Reinforcement: High strength synthetic yarn.
- 3.Cover: Ozone ,oil resistant synthetic Nitrile rubber.
- 4.Application: Soft-wall hose Designed for the delivery of petroleum-based products, diesel,gasoline,lubricants,fuel,with aromatic content up to 50%
- 5.Temperature: -32℃(-90°F) to +82℃ (+180°F)

Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

TEXTILE COVER FUEL OIL HOSE/ GLP HOSE 300PSI



- 1.Tube:Oil and fuel resistant NBR rubber.
- 2.Cover:Textile braid.
- 3.Application: It is applied to circulating diesel, bio-diesel, hydraulic oil, machinery oil and lubricating oil etc or the oil products.
- 4.Temperature: -40°C(-104°F) to + 100°C(+212°F)

Item Code	I.D	O.D	W.P		B.P		L	
	mm	mm	Bar	Psi	Bar	Psi	m	
TCF032	3.2	7	10	150	30	450	100	
TCF032	3.5	7.5	10	150	30	450	100	
TCF041	4	8	10	150	30	450	100	
TCF042	4	9	10	150	30	450	100	
TCF050	5	10	10	150	30	450	100	
TCF055	5.5	10.5	10	150	30	450	100	
TCF061	6	11	10	150	30	450	100	
TCF062	6	12	10	150	30	450	100	
TCF070	7	12	10	150	30	450	100	
TCF075	7.5	12.5	10	150	30	450	100	
TCF080	8	15	10	150	30	450	100	
TCF100	10	17	10	150	30	450	100	
TCF120	12	18	10	150	30	450	100	
TCF140	14	22	10	150	30	450	100	
TCF160	16	23	10	150	30	450	100	
TCF180	18	26	10	150	30	450	100	
TCF190	19	27	10	150	30	450	100	
TCF250	25	33	10	150	30	450	100	

NITRILE FUEL OIL DISCHARGE HOSE 150 PSI



- 1.Tube: Black,smooth,Nitrile rubber.
- 2.Reinforcement: Multiple high strength synthetic fabric
- 3.Cover: Black, wrapped surface,weather and ozoneresistant,synthetic rubber
- 5.Application: Soft-wall hose Designed for the discharge
- 6.of petroleum-based products,diesel, gasoline,lubricants,fuel,with aromatic content up to 50%.
- 5.Temperature: -32°C(-90°F) to +82°C(+180°F)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
ODH012	1/2	12.7	21	10	150	30	450	61	200
ODH016	5/8	15.9	25	10	150	30	450	61	200
ODH019	3/4	19.1	29	10	150	30	450	61	200
ODH022	7/8	22.2	31	10	150	30	450	61	200
ODH025	1	25.4	35	10	150	30	450	61	200
ODH032	1-1/4	31.8	42	10	150	30	450	61	200
ODH038	1-1/2	38.1	51	10	150	30	450	61	200
ODH050	2	50.8	64	10	150	30	450	61	200
ODH064	2-1/2	63.5	76	10	150	30	450	61	200
ODH076	3	76.2	89	10	150	30	450	61	200
ODH089	3-1/2	88.9	103	10	150	30	450	61	200
ODH100	4	101.6	116	10	150	30	450	61	200
ODH125	5	127	142	10	150	30	450	30.5	100
ODH150	6	152.4	167	10	150	30	450	30.5	100
ODH200	8	203.2	223	10	150	30	450	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
ODH3-012	1/2	12.7	22	20	300	60	900	61	200
ODH3-016	5/8	15.9	26	20	300	60	900	61	200
ODH3-019	3/4	19.1	31	20	300	60	900	61	200
ODH3-022	7/8	22.2	32	20	300	60	900	61	200
ODH3-025	1	25.4	36	20	300	60	900	61	200
ODH3-032	1-1/4	31.8	45	20	300	60	900	61	200
ODH3-038	1-1/2	38.1	51	20	300	60	900	61	200
ODH3-050	2	50.8	65	20	300	60	900	61	200
ODH3-064	2-1/2	63.5	79	20	300	60	900	61	200
ODH3-076	3	76.2	91	20	300	60	900	61	200
ODH3-089	3-1/2	88.9	107	20	300	60	900	61	200
ODH3-100	4	101.6	120	20	300	60	900	61	200
ODH3-125	5	127	148	20	300	60	900	30.5	100
ODH3-150	6	152.4	173	20	300	60	900	30.5	100
ODH3-200	8	203.2	228	20	300	60	900	30.5	100

NITRILE FUEL OIL DISCHARGE HOSE 300 PSI



- 1.Tube: Black,smooth,Nitrile.
- 2.Reinforcement: Multiple high strength synthetic fabric
- 3.Cover: Black, wrapped surface,weather and ozone resistant,synthetic rubber
- 5.Application: Soft-wall hose Designed for the discharge of petroleum-based products,diesel, gasoline,lubricants,fuel,with aromatic content up to 50%.
- 6.Temperature: -32°C(-90°F) to +82°C(+180°F)

NITRILE PETROL SUCTION HOSE150 PSI



- 1.Tube: Black,smooth,Nitrile rubber
- 2.Reinforcement: Multiple high strength synthetic fabric and steel wire helix skeleton
- 3.Cover: Black, wrapped surface,weather and ozone resistant,synthetic rubber
- 4.Application: For suction and discharge of petroleum-based products,diesel,gasoline, lubricants,fuel,with aromatic content up to 50%.
- 5.Temperature: -32°C(-90°F) to +82°C (+180°F)

Code	I.D		O.D	W.P		B.P		vacuum	L	
	inch	mm	mm	bar	psi	bar	psi	bar	m	ft
OSDH019	3/4	19.1	31	10	150	0.8	6	152	61	200
OSDH025	1	25.4	37	10	150	0.8	6	152	61	200
OSDH032	1-1/4	31.8	44	10	150	0.8	8	200	61	200
OSDH038	1-1/2	38.1	51	10	150	0.8	9	230	61	200
OSDH050	2	50.8	64	10	150	0.8	10	254	61	200
OSDH064	2-1/2	63.5	76	10	150	0.8	15	380	61	200
OSDH076	3	76.2	91	10	150	0.8	18	460	61	200
OSDH089	3-1/2	88.9	107	10	150	0.8	22	550	61	200
OSDH100	4	101.6	120	10	150	0.8	24	610	61	200
OSDH125	5	127	147	10	150	0.8	30	760	30.6	100
OSDH150	6	152.4	172	10	150	0.8	36	916	30.5	100
OSDH200	8	203.2	229	10	150	0.8	48	1200	30.5	100
OSDH254	10	254	282	10	150	0.8	50	1250	11.8	39
OSDH300	12	304.8	329	10	150	0.8	60	1520	11.8	39



Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

NITRILE PETRO SUCTION HOSE
300 PSI



- 1.Tube: Black,smooth,Nitrile rubber
- 2.Reinforcement: Multi plies high strength synthetic fabric and steel wire helix skeleton
- 3.Cover: Black, wrapped surface,weather and ozone resistant,synthetic rubber
- 4.Application: For suction and discharge of petroleum-based products,diesel,gasoline, lubricants,fuel,with aromatic content up to 50%.
- 5.Temperature: -32°C(-90°F) to + 82°C (+180°F)

NITRILE PETROL SUCTION
HOSE 400 PSI



Code	I.D		O.D	W.P		B.P		vacuum	L	
	inch	mm	mm	bar	psi	bar	psi	bar	m	ft
OSDH3019	3/4	19.1	32	20	300	0.8	6	152	61	200
OSDH3025	1	25.4	37	20	300	0.8	6	152	61	200
OSDH3032	1-1/4	31.8	47	20	300	0.8	8	200	61	200
OSDH3038	1-1/2	38.1	54	20	300	0.8	9	230	61	200
OSDH3050	2	50.8	67	20	300	0.8	10	254	61	200
OSDH3064	2-1/2	63.5	80	20	300	0.8	15	380	61	200
OSDH3076	3	76.2	92	20	300	0.8	18	460	61	200
OSDH3089	3-1/2	88.9	110	20	300	0.8	22	550	61	200
OSDH3100	4	101.6	122	20	300	0.8	24	610	61	200
OSDH3125	5	127	153	20	300	0.8	30	760	30.5	100
OSDH3150	6	152.4	176	20	300	0.8	36	916	30.5	100
OSDH3200	8	203.2	228	20	300	0.8	48	1200	30.5	100
OSDH3254	10	254	288	20	300	0.8	50	1250	11.8	39
OSDH3304	12	304.8	340	20	300	0.8	60	1520	11.8	39

Code	I.D		O.D	W.P		ACUU	R		L	
	inch	mm	mm	bar	psi	bar	inch	mm	m	ft
OSDH4050	2	50.8	67	27.6	400	0.8	10	254	61	200
OSDH4064	2-1/2	63.5	80	27.6	400	0.8	15	380	61	200
OSDH4076	3	76.2	92	27.6	400	0.8	18	460	61	200
OSDH4089	3-1/2	88.9	110	27.6	400	0.8	22	550	61	200
OSDH4100	4	101.6	122	27.6	400	0.8	24	610	61	200

- 1.Tube: Black,smooth,Nitrile rubber
- 2.Reinforcement: Multi plies high strength synthetic fabric and steel wire helix skeleton
- 3.Cover: Black, wrapped surface,weather and ozone resistant,synthetic rubber
- 4.Application: For suction and discharge of petroleum-based products,diesel,gaso line, lubricants,fuel,with aromatic content up to 50%.
- 5.Temperature: -32°C (-90°F) to +82°C (+180°F)

TANK TRUCK OIL HOSE 150PSI



Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
TTOH050	2"	50.8	63	10	150	30	450	61	200
TTOH064	2-1/2"	63.5	76	10	150	30	450	61	200
TTOH076	3"	76.2	89	10	150	30	450	61	200
TTOH089	3-1/2"	88.9	103	10	150	30	450	61	200
TTOH100	4"	101.6	120	10	150	30	450	61	200
TTOH125	5"	127	147	10	150	30	450	30.5	100
TTOH150	6"	152.4	172	10	150	30	450	30.5	100

- 1.Tube: Black,smooth,Nitrile rubber
- 2.Reinforcement: High strength synthetic fabric and helix wire,with anti-static wire
- 3.Cover:Black or Red,smooth or corrugated oil,fuel,and weathering resistant synthetic rubber
- 4.Application: Hardwall hose designed for suction and delivery of a wide range of petroleum fuel with aromatic content up to 50% for tank trucks.
- 5.Temperature: -32°C (-90°F) to +82°C (+180°F)

Code	I.D		O.D	W.P		ACUU	R		L	
	inch	mm	mm	bar	psi	bar	inch	mm	m	ft
NPSDH050	2"	50.8	71	40	600	0.8	12	305	61	200
NPSDH063	2-1/2"	63.5	87.6	40	600	0.8	15	381	61	200
NPSDH076	3"	76.2	99.6	40	600	0.8	18	457.2	61	200
NPSDH088	3-1/2"	88.9	112.2	40	600	0.8	21	533	61	200
NPSDH101	4"	101.6	128.4	40	600	0.8	24	610	61	200
NPSDH152	6"	152	183.4	40	600	0.8	36	915	30.5	100

- 1.Tube: Black,smooth,Nitrile rubber
- 2.Reinforcement: Multi plies high strength synthetic fabric and steel wire helix skeleton
- 3.Cover: Black, wrapped surface,weather and ozone resistant,synthetic rubber
- 4.Temperature:-32°C to +82°C(-90°F to +180°F)
- 5.Application: For suction and discharge of petroleum-based products,diesel, gasoline, lubricants,fuel,with aromatic content up to 50%.

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
DOT076	3"	76.2	96	20	300	60	900	61	200
DOT100	4"	101.6	126	20	300	60	900	61	200
DOT125	5"	127	155	20	300	60	900	30.5	100
DOT150	6"	152.4	185	20	300	60	900	30.5	100
DOT200	8"	203.2	242	20	300	60	900	11.8	39
DOT250	10"	254	298	20	300	60	900	11.8	39

- 1.Tube: Black,smooth,Nitrile synthetic rubber, suitable for up to 50% aromatic content
- 2.Reinforcement: Multiply heavy duty synthetic tire cord supported with helix wire, anti-static wires
- 3.Temperature: -40°C to +100°C (+180°F)
- 4.Cover:Black,wrapped finish,synthetic rubber for high abrasion ,ozone & weather resistance
- 5.Application: Heavy duty suction and discharge dock hose designed for transferring petroleum product up to 50%aromatic content from tankers and barges,bunkering service and industrial applications.

Code	I.D		O.D	W.P		B.P		L	Weight
	inch	mm	mm	bar	psi	bar	psi	mm	kg/m
FDH016	5/8"	15.9	25.4	18	258	72	1032	160	0.59
FDH019	3/4"	19.1	28.7	18	258	72	1032	190	0.67
FDH025	1"	25.4	35.1	18	258	72	1032	240	0.89

- 1.Tube: Nitrile synthetic rubber,smooth
- 2.Reinforcement: steel wire braid
- 3.Cover: Nitrile synthetic rubber,black,green, red,blue or yellow
- 4.Application: Designed for general refueling equipment to convey aviation kerosene gasoline,diesel oil and other mineral oil.
- 5.Temperature: -40°C(-104°F) to 121°C (+250°F)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
HTSH051	2"	50.8	69	10	150	30	450	61	200
HTSH076	3"	76.2	96	10	150	30	450	61	200
HTSH102	4"	101.6	122	10	150	30	450	61	200

- 1.Tube: Black,smooth,special elastmoer compound
- 2.Reinforcement:2 or 4 layers high tensile cord with steel wire helix, anti-static wires
- 3.Cover:Black,wrapped finish,synthetic elastomer compound for high abrasion ozone & weather resistance
- 4.Application: Hot tar and alphalt suction hose is specially designed for conveying hot tar and asphalt.
- 5.Temperature: -40°C(-22°F) to 180°C (+356°F)

NITRILE PETROL SUCTION
HOSE 40BAR



DOCK OIL TRANSFER HOSE
BUNKERING HOSE



FUEL DISPENSER PUMP HOSE



HOT TAR & ASPHALT SUCTION
HOSE 150PSI



Chemical Discharge Hose
150Psi



- 1.Tube: White,Smooth Ultra High Molecular Weight Polyethylene (UHMWPE),EPDM.
- 2.Reinforcement: Multi plies high strength synthetic fabric
- 3.Cover:EPDM resistant to chemical weathering and ozone,blue,green wrapped.
- 4.Application: Designed for in-plant or tank truck use to transfer chemicals and solvents.
- 5.Temperature: -40℃ (-72 ℉) to + 120℃ (+248 ℉)

Chemical Discharge Hose
250Psi



- 1.Tube: White,Smooth Ultra High Molecular Weight Polyethylene (UHMWPE),EPDM.
- 2.Reinforcement: Multi plies high strength synthetic fabric
- 3.Cover:EPDM resistant to chemical weathering and ozone,blue,green wrapped.
- 4.Application: Designed for in-plant or tank truck use to transfer chemicals and solvents.
- 5.Temperature: -40℃ (-72 ℉) to + 120℃ (+248 ℉)

Chemical Suction Hose 150Psi



- 1.Tube: White,Smooth Ultra High Molecular Weight Polyethylene (UHMWPE), EPDM.
- 2.Reinforcement: Multi plies high strength synthetic fabric and helix wire
- 3.Cover:EPDM resistant to chemical, weathering and ozone,blue,green wrapped or corrugated
- 4.Application: Designed for in-plant or tank truck use ,suction and discharge of chemicals and solvents.
- 5.Temperature: -40℃ (-72 ℉) to + 120℃ (+248 ℉)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
UCDH019	3/4"	19.1	31	10	150	40	600	61	200
UCDH025	1"	25.4	37	10	150	40	600	61	200
UCDH032	1-1/4"	31.8	44	10	150	40	600	61	200
UCDH038	1-1/2"	38.1	51	10	150	40	600	61	200
UCDH050	2"	50.8	67	10	150	40	600	61	200
UCDH064	2-1/2"	63.5	79	10	150	40	600	61	200
UCDH076	3"	76.2	92	10	150	40	600	61	200
UCDH089	3-1/2"	88.9	105	10	150	40	600	61	200
UCDH102	4"	101.6	118	10	150	40	600	61	200
UCDH152	6"	152	175	10	150	40	600	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
UCDH2019	3/4"	19.1	31	17	250	68	1000	61	200
UCDH2025	1"	25.4	37	17	250	68	1000	61	200
UCDH2032	1-1/4"	31.8	44	17	250	68	1000	61	200
UCDH2038	1-1/2"	38.1	51	17	250	68	1000	61	200
UCDH2050	2"	50.8	67	17	250	68	1000	61	200
UCDH2064	2-1/2"	63.5	79	17	250	68	1000	61	200
UCDH2076	3"	76.2	92	17	250	68	1000	61	200
UCDH2089	3-1/2"	88.9	105	17	250	68	1000	61	200
UCDH2102	4"	101.6	118	17	250	68	1000	61	200
UCDH2152	6"	152	175	17	250	68	1000	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
UCSH019	3/4"	19.1	30	10	150	40	600	61	200
UCSH025	1"	25.4	36	10	150	40	600	61	200
UCSH032	1-1/4"	31.8	44	10	150	40	600	61	200
UCSH038	1-1/2"	38.1	51	10	150	40	600	61	200
UCSH050	2"	50.8	64	10	150	40	600	61	200
UCSH064	2-1/2"	63.5	79	10	150	40	600	61	200
UCDH076	3"	76.2	92	10	150	40	600	61	200
UCDH089	3-1/2"	88.9	105	10	150	40	600	61	200
UCDH102	4"	101.6	120	10	150	40	600	61	200
UCDH152	6"	152	172	10	150	40	600	30.5	100

Chemical Suction Hose 250Psi



- 1.Tube: White,Smooth Ultra High Molecular Weight Polyethylene (UHMWPE), EPDM.
- 2.Reinforcement: Multi plies high strength synthetic fabric and helix wire
- 3.Cover:EPDM resistant to chemical, weathering and ozone,blue,green wrapped or corrugated
- 4.Application: Designed for in-plant or tank truck use ,suction and discharge of chemicals and solvents.
- 5.Temperature: -40℃ (-72 ℉) to + 120℃ (+248 ℉)

Food Discharge Hose 150Psi



- 1.Tube: White,smooth,NR,NBR or EPDM food quality rubber
- 2.Reinforcement: High strength synthetic fabric
- 3.Cover: smooth(wrapped finish),synthetic rubber, blue or white,weathering resistant.
- 4.Application: FDA approved food hose designed for the delivery of foods such as milk Juice,beer,edible oil,dairy products etc.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
UCSH2019	3/4"	19.1	31	17	250	68	1000	61	200
UCSH2025	1"	25.4	38	17	250	68	1000	61	200
UCSH2032	1-1/4"	31.8	47	17	250	68	1000	61	200
UCSH2038	1-1/2"	38.1	53	17	250	68	1000	61	200
UCSH2050	2"	50.8	67	17	250	68	1000	61	200
UCSH2064	2-1/2"	63.5	82	17	250	68	1000	61	200
UCDH2076	3"	76.2	94	17	250	68	1000	61	200
UCDH2089	3-1/2"	88.9	108	17	250	68	1000	61	200
UCDH2102	4"	101.6	122	17	250	68	1000	61	200
UCDH2152	6"	152	175	17	250	68	1000	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
FDH012	1/2"	12.7	22	10	150	30	450	61	200
FDH019	3/4"	19.1	29	10	150	30	450	61	200
FDH025	1"	25.4	37	10	150	30	450	61	200
FDH032	1-1/4"	31.8	43	10	150	30	450	61	200
FDH038	1-1/2"	38.1	50	10	150	30	450	61	200
FDH050	2"	50.8	64	10	150	30	450	61	200
FDH064	2-1/2"	63.5	78	10	150	30	450	61	200
FDH076	3"	76.2	90	10	150	30	450	61	200
FDH089	3-1/2"	89	104	10	150	30	450	61	200
FDH102	4"	101.6	116	10	150	30	450	61	200

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
FDH2012	1/2"	12.7	22	17	250	51	750	61	200
FDH2019	3/4"	19.1	31	17	250	51	750	61	200
FDH2025	1"	25.4	38	17	250	51	750	61	200
FDH2032	1-1/4"	31.8	45	17	250	51	750	61	200
FDH2038	1-1/2"	38.1	51	17	250	51	750	61	200
FDH2050	2"	50.8	68	17	250	51	750	61	200
FDH2064	2-1/2"	63.5	79	17	250	51	750	61	200
FDH2076	3"	76.2	91	17	250	51	750	61	200
FDH2089	3-1/2"	89	106	17	250	51	750	61	200
FDH2102	4"	101.6	120	17	250	51	750	61	200

Food Discharge Hose 250Psi



- 1.Tube: White,smooth,NR,NBR or EPDM food quality rubber
- 2.Reinforcement: High strength synthetic fabric
- 3.Cover: smooth(wrapped finish),synthetic rubber, blue or white,weathering resistant.
- 4.Application: FDA approved food hose designed for the delivery of foods such as milkJuice,beer,edible oil,dairy products etc.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

Food Suction and delivery Hose
150Psi



- 1.Tube:White,smooth,NR,NBR or EPDM food quality rubber
- 2.Reinforcement:Multi plies high strength synthetic fabric and helix wire
- 3.Cover:smooth(wrapped finish),synthetic rubber, blue or white,weathering resistant.
- 4.Application: FDA approved food hose designed for the suction and delivery of foods such as milk,Juice,beer,edible oil, dairy products etc.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

Food Suction and delivery Hose
250Psi



- 1.Tube:White,smooth,NR,NBR or EPDM food quality rubber
- 2.Reinforcement:Multi plies high strength synthetic fabric and helix wire
- 3.Cover:smooth(wrapped finish),synthetic rubber, blue or white,weathering resistant.
- 4.Application: FDA approved food hose designed for the suction and delivery of foods such as milk,Juice,beer,edible oil, dairy products etc.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

Oxygen Hose 300PSI



- 1.Tube:Black, smooth, synthetic rubber
- 2.Reinforcement:High strength synthetic plies
- 3.Cover:Blue/green/red, smooth, synthetic rubber
- 4.Application: Designed for welding, cutting and allied processes. Specific welding hose cartering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
FSH019	3/4"	19.1	31	10	150	30	450	61	200
FSH025	1"	25.4	37	10	150	30	450	61	200
FSH032	1-1/4"	31.8	44	10	150	30	450	61	200
FSH038	1-1/2"	38.1	51	10	150	30	450	61	200
FSH050	2"	50.8	64	10	150	30	450	61	200
FSH064	2-1/2"	63.5	80	10	150	30	450	61	200
FSH076	3"	76.2	92	10	150	30	450	61	200
FSH089	3-1/2"	89	105	10	150	30	450	61	200
FSH102	4"	101.6	120	10	150	30	450	61	200
FSH125	5"	125	145	10	150	30	450	30.5	100
FSH152	6"	152	172	10	150	30	450	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
FSH2019	3/4"	19.1	32	17	250	51	750	61	200
FSH2025	1"	25.4	38	17	250	51	750	61	200
FSH2032	1-1/4"	31.8	46	17	250	51	750	61	200
FSH2038	1-1/2"	38.1	53	17	250	51	750	61	200
FSH2050	2"	50.8	67	17	250	51	750	61	200
FSH2064	2-1/2"	63.5	81	17	250	51	750	61	200
FSH2076	3"	76.2	93	17	250	51	750	61	200
FSH2089	3-1/2"	89	107	17	250	51	750	61	200
FSH2102	4"	101.6	122	17	250	51	750	61	200
FSH2125	5"	125	147	17	250	51	750	30.5	100
FSH2152	6"	152	174	17	250	51	750	30.5	100

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
OXYH005	3/16"	4.8	12	20	300	60	900	100	330
OXYH006	1/4"	6.4	13	20	300	60	900	100	330
OXYH008	5/16"	7.9	15	20	300	60	900	100	330
OXYH010	3/8"	9.5	17	20	300	60	900	100	330
OXYH012	1/2"	12.7	21	20	300	60	900	100	330
OXYH016	5/8"	15.9	26	20	300	60	900	100	330
OXYH019	3/4"	19.1	29	20	300	60	900	100	330
OXYH025	1"	25.4	36	20	300	60	900	100	330

Acetylene Hose 300PSI



- 1.Tube:Black, smooth, synthetic rubber
- 2.Reinforcement:High strength synthetic plies
- 3.Cover:Blue/green/red, smooth, synthetic rubber
- 4.Application: Designed for welding, cutting and allied processes. Specific welding hose cartering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

RUBBER TWIN WELDING HOSE
300 PSI



- 1.Tube : Black, smooth, synthetic rubber
- 2.Reinforcement:High strength synthetic yarn braiding
- 3.Cover:Blue/green/red, smooth, synthetic rubber
- 4.Application: Designed for welding, cutting and allied processes. Specific welding hose cartering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.
- 5.Temperature: -32℃ (-90 ℉) to 80℃ (+176 ℉)

RUBBER LPG/ PROPANE/GAS
HOSE 300 PSI



Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
ACEH005	3/16"	4.8	12	20	300	60	900	100	330
ACEH006	1/4"	6.4	13	20	300	60	900	100	330
ACEH008	5/16"	7.9	15	20	300	60	900	100	330
ACEH010	3/8"	9.5	17	20	300	60	900	100	330
ACEH012	1/2"	12.7	21	20	300	60	900	100	330
ACEH016	5/8"	15.9	26	20	300	60	900	100	330
ACEH019	3/4"	19.1	29	20	300	60	900	100	330
ACEH025	1"	25.4	36	20	300	60	900	100	330

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
TWH005	3/16"	4.8+4.8	12+12	20	300	60	900	100	330
TWH006	1/4"	6.4+6.4	13+13	20	300	60	900	100	330
TWH008	5/16"	7.9+7.9	15+15	20	300	60	900	100	330
TWH810	5/16"+3/8"	7.9+9.5	15+17	20	300	60	900	100	330
TWH010	3/8"	9.5+9.5	17+17	20	300	60	900	100	330

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
GASH005	3/16"	4.8	12	20	300	60	900	100	330
GASH006	1/4"	6.4	13	20	300	60	900	100	330
GASH008	5/16"	7.9	15	20	300	60	900	100	330
GASH010	3/8"	9.5	17	20	300	60	900	100	330
GASH012	1/2"	12.7	21	20	300	60	900	100	330

Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

RUBBER SANDBLAST HOSE
12BAR



- 1.Tube:Black,smooth, NR synthetic rubber
- 2.Reinforcement: Multiple High strength synthetic textile cards.
- 3.Cover:Black, smooth(wrapped), abrasion resistant NR synthetic rubber
- 4.Application: oft-wall abrasion resistant hose designed for the delivery of steel shots, sand, bead blasting application
- 5.Temperature: -40 C to +70 C (-40 F to + 158 F)

BULK MATERIAL SUCTION
HOSE 150PSI



- 1.Tube: Pure gum compound
- 2.Reinforcement: Multiple synthetic fabric with steel wire helix
- 3.Cover:Black synthetic rubber, fabric impression, corrugated or smooth.
- 4.Application: For suction, discharge or gravity flow of abrasives ,dry cement,sand, gravel etc from manufacturing, sandblast recovery, mineral processing, power plants.
- 5.Temperature: -40°C to +82°C(-40°F to +180°F)

BULK MATERIAL DISCHARGE
HOSE



- 1.Tube:Black,smooth, NR synthetic rubber
- 2.Reinforcement: Multi ply High strength synthetic fabric
- 3.Cover:Black, smooth(wrapped), abrasion resistant NR synthetic rubber
- 4.Application: Softwall abrasion resistant hose designed for the delivery of steel shots, sand, bead blasting application
- 5.Temperature: -40 C to +70 C (-40 F to +158 F)

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
SBH012	1/2"	12.7	25	12	174	36	522	40	131
SBH016	5/8"	15.9	30	12	174	36	522	40	131
SBH019	3/4"	19.1	34	12	174	36	522	40	131
SBH025A	1"	25.4	38	12	174	36	522	40	131
SBH025B	1"	25.4	47	12	174	36	522	40	131
SBH032	1-1/4"	31.8	48	12	174	36	522	40	131
SBH038	1-1/2"	38.1	54	12	174	36	522	40	131
SBH051	2"	50.8	69	12	174	36	522	40	131
SBH064	2-1/2"	64	84	12	174	36	522	40	131
SBH076	3"	76.2	96	12	174	36	522	40	131
SBH102	4"	102	124	12	174	36	522	40	131
SBH127	5"	127	149	12	174	36	522	40	131
SBH152	6"	152	177	12	174	36	522	40	131

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
BMSH032	1 1/4"	31.8	46	10	150	30	300	61	200
BMSH038	1 1/2"	38	53	10	150	30	300	61	200
BMSH051	2"	50	69	10	150	30	300	61	200
BMSH064	2-1/2"	64	83	10	150	30	300	61	200
BMSH076	3"	76	98	10	150	30	300	61	200
BMSH089	3-1/2"	89	113	10	150	30	300	61	200
BMSH102	4"	102	126	10	150	30	300	61	200
BMSH127	5"	127	153	10	150	30	300	30.5	100
BMSH152	6"	152	180	10	150	30	300	30.5	100
BMSH203	8"	203	235	10	150	30	300	12	40
BMSH254	10"	254	287	10	150	30	300	12	40
BMSH304	12"	304.8	335	10	150	30	300	12	40

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
BMDH050	2"	50.8	68	10	150	30	450	60	200
BMDH057	2-1/4"	57.2	74	10	150	30	450	60	200
BMDH060	1-3/8"	60.3	77	10	150	30	450	60	200
BMDH063	2-1/2"	63.5	81	10	150	30	450	60	200
BMDH066	2-5/8"	66.7	84	10	150	30	450	40	130
BMDH069	2-3/4"	69.9	88	10	150	30	450	40	130
BMDH076	3"	76.2	94	10	150	30	450	60	100
BMDH089	3-1/2"	88.9	107	10	150	30	450	60	100
BMDH102	4"	101.6	120	10	150	30	450	30	100
BMDH114	4-1/2"	114.3	134	10	150	30	450	30	100
BMDH127	5"	127	148	10	150	30	450	30	100
BMDH152	6"	152.4	175	10	150	30	450	30	100
BMDH203	8"	203.2	230	10	150	30	450	30	100
BMDH254	10"	254	281	10	150	30	450	12	40
BMDH304	12"	304.8	334	10	150	30	450	12	40

Code	I.D		O.D	W.P		L	
	mm	inch	mm	psi	bar	ft	m
CPH5551	51	2	74	800	55	200	61
CPH5576	76	3	100	800	55	200	61
CPH55102	102	4	132	800	55	200	61

- 1.Tube: Black NR/SBR rubber compound

2.Reinforcement: Multi ply synthetic fabric or steel wire braiding

3.Cover: Black,smooth cloth impression, NR/SBR rubber compound
- 4.Application: These concrete hoses are high pressure pumping components designed to pump concrete and other abrasive mixtures such as plaster and wet cement at a pressure up to 800psi

5.Temperature: -40 C to +70 C (-20 F to +80 F)

Code	I.D		O.D		W.P		B.P		R		Weight
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm	kg/m
CPH8551	2	50.8	2.75	69.8	1230	8.5	3000	20	10.83	275	3.03
CPH8564	2 1/2	63.5	3.46	88	1230	8.5	3000	20	11.81	300	4.48
CPH8576	3	76.2	3.81	96.7	1230	8.5	3000	20	13.78	350	5.46
CPH85102	4	101.6	5.12	130	1230	8.5	3000	20	15.75	400	8.46
CPH85127	5	127	6.1	155	1230	8.5	3000	20	19.69	500	9.63
CPH85152	6	152.4	7.09	180	1230	8.5	3000	20	25.59	600	10.99

- 1.Tube: Black,smooth,Abrasion resistant NR/SBR compound

2.Reinforcement: 2"-3" : two steel wire braiding, 3 1/2"-6" four layers steel cords

3.Temperature: -40 C to +70 C (-40 F to +158 F)
- 4.Cover:Black,smooth cloth impression, NR/SBR compound abrasion cover,resistant to abrasion, cutting, gouging and weather.

5.Application: High pressure concrete placement application.

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
LCDH076	3	76	86	4	60	12	180	20	65
LCDH089	3-1/2"	89	100	4	60	12	180	20	65
LCDH102	4	102	112	4	60	12	180	20	65
LCDH127	5	127	137	4	60	12	180	20	65
LCDH152	6	152	162	4	60	12	180	20	65
LCDH203	8	203	213	4	60	12	180	20	65

- 1.Tube: Black,smooth,NR/SBR rubber compound

2.Reinforcement: 2 ply high tensile synthetic fabric
- 3.Cover:Black,smooth,cloth impression NR/SBR rubber compound,abrasion and weather resistant

4.Application: Layflat delivery hose for concrete sand,gravel and general abrasive dry materials

CONCRETE PLACEMENT HOSE
800PSI



CONCRETE PLACEMENT HOSE
85BAR/1230PSI



LAYFLAT CEMENT DISCHARGE
HOSE 60PSI



Hose

Ferrule

Fitting JIC

Fitting ORFS

Fitting NPT

Fitting SAE

Fitting BSP

Fitting Flange

Fitting Metric

Fitting JIS

Adapter

Quick Coupling

Camlock

Hose Clamp

Machine

EPDM STEAM HOSE 230℃



- 1.Tube: Synthetic rubber EPDM
- 2.Reinforcement: high tensile wire braiding
- 3.Cover:Red or blue, pin pricked smooth (wrapped finish) ,EPDM rubber
- 4.Application: The steam hose is used for the saturated steam in chemical industry, petroleum industry, shipbuilding industry

Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
RSTH2010	10	3/8"	21	17	250	170	2500	50	0.45
RSTH2012	12	1/2"	25	17	250	170	2500	60	0.53
RSTH2016	16	5/8"	28	17	250	170	2500	70	0.6
RSTH2019	19	3/4"	32	17	250	170	2500	80	0.68
RSTH2025	25	1"	39	17	250	170	2500	110	0.9
RSTH2032	32	1 1/4"	46	17	250	170	2500	150	1.3
RSTH2038	38	1 1/2"	54	17	250	170	2500	180	1.6
RSTH2051	51	2"	67	17	250	170	2500	245	2.2
RSTH2064	64	2 1/2"	83	17	250	170	2500	300	3.8
RSTH2076	76	3"	95	17	250	170	2500	400	4.6
RSTH2089	89	3 1/2"	110	17	250	170	2500	500	5.2
RSTH2102	102	4"	124	17	250	170	2500	600	6.5


EPDM STEAM HOSE 170℃



- 1.Tube: Black EPDM rubber.
- 2.Reinforcement: Multiple layers of heat resistant textile cord.
- 3.Cover: Black EPDM rubber (wrapped finish; pin pricked to prevent blistering).
- 4.Temperature: -30℃ (-22°F) to +170℃ (338°F)
- 5.Application: Hot water hose suitable for many applications in automobile industry,cleaning equipment,cooling systems
- 6.Characteristic: resistant to heat,ozone, anti-freeze,and weathering

Hose Type	I.D.		O.D.	Wall Thick	Wall Diff	Expansion ml/Max.mm		Burst pressure
Dash	mm		mm	mm	Bar	6.9mpa	10.3mpa	Mini mpa
1	3.3	+0.2 -0.1	10.5	+0.3 -0.2	3.65	<0.25	<1.08	<1.38
2	4.8±0.2		13±0.3		4.35	<0.3	<1.81	<2.36
3	6.3±0.2		15±0.3		3.75	<0.3	<2.69	<3.84

AIR BRAKE HOSE



SAE J1402 Air Pressure Brake Hose
Working temperature range :-40℃ ~+120℃

Hose Type	I.D.	O.D.	Wall Thickness	Wall Diff Max	Working pressure	Burst pressure
Dash	mm	mm	mm	Bar	MPa	Mini
1	5.0±0.2	14.0±0.2	4.50	0.3	1.4	>12
2	6.0±0.2	15.0±0.4	4.50	0.3	1.4	>12
3	8.0±0.2	15.0±0.3	3.50	0.3	1.4	>12
4	10.0±0.4	17.0±0.4	3.75	0.3	1.4	>12
5	13.0±0.4	23.0±0.4	3.50	0.4	1.4	>12
6	16.0±0.5	24.0±0.5	4.00	0.4	1.4	>12


Hose Type	I.D.	O.D.	Wall Thickness	Wall Diff Max	Vacuum Degree	Burst pressure
Dash	mm	mm	mm	Bar	Max Mpa	Mini mpa
1	8.0±0.2	14.0±0.4	3.00	0.3	>66.7	>2.4
2	9.0±0.2	17.0±0.4	4.00	0.3	>66.7	>2.4
3	10.0±0.2	17.0±0.3	3.50	0.3	>66.7	>2.4
4	11.0±0.4	19.0±0.4	4.00	0.3	>66.7	>2.4
5	12.0±0.4	19.0±0.4	3.50	0.3	>66.7	>2.4
6	16.0±0.5	24.0±0.5	4.00	0.4	>66.7	>2.4

Hose Type	Dimension		I.D.	O.D.	Wall Thick ness	Wall Diff Max	Working Pres	Bursting Press	Bend Radi	Wei gh	Prem eabil ity
Dash	mm	Inch	mm	mm	mm	mm	mpa	mpa	mm	g/m	Kg/
C8.0	8.0	5/16"	8.0±0.4	15.2±0.5	3.6	0.4	3.5	23.0	55	146	1.6
C10.0	10.0	13/32"	10.2±0.3	17.2±0.4	3.5	0.4	3.5	22.0	65	178	1.6
C11.5	11.4	13/32"	11.4±0.4	18.4±0.5	3.5	0.4	3.5	22.0	70	196	1.6
C13.0	13.0	1/2"	13.2±0.4	21.0±0.5	4.0	0.4	3.5	20.0	75	231	1.6
C15.2	15.2	5/8"	15.2±0.4	23.0±0.5	3.9	0.4	3.5	21.0	85	257	1.6
CH8.0	8.2	5/16"	8.2±0.4	19.0±0.5	5.4	0.4	3.5	21.0	70	285	1.6
CH10.5	10.5	13/32"	10.5±0.4	23.0±0.5	6.3	0.4	3.5	21.0	85	393	1.6
CH13a	13.0	1/2"	13.0±0.4	25.4±0.5	6.2	0.4	3.5	22.0	85	332	1.6
CH13b	13.0	1/2"	13.0±0.4	23.0±0.5	5.0	0.4	3.5	22.0	95	441	1.6
CH16	16.1	5/8"	16.1±0.4	28.6±0.5	6.3	0.4	3.5	18.0	105	470	1.6
C19	19.0	3/4"	19.0±0.5	28.5±0.6	4.8	0.4	1.5	18.0	105	428	1.6
C22	22.2	7/8"	22.2±0.5	33.3±0.7	5.6	0.5	1.5	16.0	125	671	1.6
C28.5	28.5	9/8"	28.7±0.5	39.7±0.8	5.5	0.5	1.5	12.0	150	831	1.6

Hose Type	Dimension		I.D.	O.D.	Wall Thic	Wall Diff	Working	Bursting	Bend	Wei gh	Prem eabi
Dash	mm	Inch	mm	mm	mm	mm	mpa	mpa	mm	g/m	Kg/
BH8.0	8.2	5/16"	8.2±0.4	18.7±0.5	5.3	0.4	3.5	20.0	55	261	1.6
BH10.5	10.5	13/32"	10.5±0.4	22.5±0.5	6.0	0.4	3.5	23.0	85	411	1.6
BH13	13.0	1/2"	13.0±0.4	23.0±0.5	5.0	0.4	3.5	22.0	90	485	1.6
BH16	16.0	5/8"	16.0±0.5	28.0±0.6	6.0	0.4	3.5	21.0	105	558	1.6
A8.0	8.2	5/16"	8.0±0.3	15.2±0.4	3.5	0.4	3.5	23.0	55	155	1.6
A10.0	10.0	13/32"	10.2±0.3	17.2±0.4	3.5	0.4	3.5	22.0	65	178	1.6
A10.5	10.5	13/32"	10.5±0.3	18.7±0.4	4.1	0.4	3.5	22.0	75	195	1.6
A11.5	11.5	13/32"	11.5±0.3	18.5±0.4	3.5	0.4	3.5	23.0	75	201	1.6
A13	13.0	1/2"	13.0±0.3	20.6±0.4	3.8	0.4	3.5	22.0	75	241	1.6
A13.2	13.2	1/2"	13.2±0.3	20.8±0.4	3.8	0.4	3.5	22.0	75	241	1.6
A15.2	15.2	5/8"	15.5±0.4	22.8±0.4	3.8	0.4	3.5	20.0	85	271	1.6
A15.5	15.5	5/8"	15.3±0.4	22.8±0.5	4.0	0.4	3.5	20.0	90	284	1.6
A19	19.0	3/4"	19.5±0.5	28.5±0.6	4.8	0.4	1.5	18.0	105	428	1.6
A22	22.2	7/8"	22.2±0.5	33.3±0.7	5.6	0.5	1.5	16.0	125	671	1.6
A28.5	28.5	9/8"	28.7±0.6	39.7±0.8	5.5	0.5	1.5	12.0	150	831	1.6


Hose Type	Dimension		O.D.	Wall Thicknes s	Wall Diff Max mm.	Working Pressure	Bursting Pressure
Dash	mm	Inch	mm	mm	mm	mpa	mpa
1	9.8±0.3	3/8"	19.8±0.5	5.0	0.4	10.3	58
2	9.8±0.3	3/8"	18.2±0.5	4.2	0.4	10.3	55

VACUUM BRAKE HOSE




SAE J1403 Vacuum Hose
Working temperature range : -40℃ ~+100℃

Type C Air Conditioning Hose




Type C Air Conditioning Hose
Appliable refrigerant : R 134a / R 1234yf
Standard :SAE J2064 SAE J3062
Working temperature range :-40℃ ~+135℃

Type E Air Conditioning Hose



Type E Air Conditioning Hose
Appliable refrigerant :R 134a / R 404a / R 1234yf / R32 / R290
Standard :SAE J2064 SAE J3062
Working temperature range :-40℃ ~+135℃

POWER STEERING HOSE



High Pressure Power Steering Hose
Standard :SAE J188
Working temperature range :-40℃ ~+135℃

Hose
Ferrule
Fitting JIC
Fitting ORFS
Fitting NPT
Fitting SAE
Fitting BSP
Fitting Flange
Fitting Metric
Fitting JIS
Adapter
Quick Coupling
Camlock
Hose Clamp
Machine



Silicone One meter hose



Straight length silicone hose



45 degrees elbow silicone hose



67 degrees elbow silicone hose



90 degrees elbow silicone hose



135 degrees elbow silicone hose



180 degrees elbow silicone hose



Straight reducer



45 degrees elbow reducer



90 degrees reducer



Silicone hump hose



Silicone heater hose



Silicone corrugated hose



Silicone Tshape hose



Silicone vacuum hose

SILICONE HOSE OEM/ODM

- ✓ With Standard High Temperature and Pressure
- ✓ Full Range of Size
- ✓ Manufacturer Sales and ISO9001:2015

BLUE

RED

PINK

YELLOW

WHITE

GREEN

BLACK

PURPLE

ORANGE

Hose
Ferrule
Fitting JIC
Fitting ORFS
Fitting NPT
Fitting SAE
Fitting BSP
Fitting Flange
Fitting Metric
Fitting JIS
Adapter
Quick Coupling
Camlock
Hose Clamp
Machine